

COMSPHERE[®] 3825PLUS

SOFTWARE-DEFINED (SD)
33.6 Kbps V.34 MODEM



B E N E F I T S

- **SAVES TIME AND MONEY.** AT 33.6 Kbps, THE 3825PLUS SAVES TIME AND MONEY ON THE PUBLIC NETWORK
- **ECONOMICALLY EXTENDS FUNCTIONALITY.** REMOTE END USERS CAN NOW TAKE ADVANTAGE OF THE SAME FULL-FEATURED FUNCTIONALITY THAT CORPORATE NETWORK USERS REQUIRE
- **PROTECTS YOUR INVESTMENT.** COMPLETELY RECONFIGURABLE; ACCEPTS UPGRADES AND ENHANCEMENTS VIA SIMPLE SOFTWARE DOWNLOADS
- **SIMPLIFIES CONTROL.** QUICKLY CONFIGURE OR CLONE COMSPHERE MODEMS REMOTELY FROM A CENTRAL LOCATION
- **NETWORK MANAGED.** MANAGE, TEST, TROUBLESHOOT, AND GATHER INFORMATION FROM REMOTE COMSPHERE MODEMS WITH THE COMSPHERE 6700 NMS
- **SECURES DATA.** TWO LEVELS OF PASSWORDS, A CALL-SCREENING/CALL-BACK FEATURE, AND SILENT ANSWERING GIVE YOUR DATA TRANSFERS SEVERAL LEVELS OF SECURITY
- **UNSURPASSED PERFORMANCE AND RELIABILITY.** 3825PLUS' TECHNOLOGY HAS UNDERGONE EXTENSIVE TESTING TO ASSURE ACCURACY, RELIABILITY, AND UNSURPASSED COMPATIBILITY

The COMSPHERE 3825Plus is Paradyne's most affordable V.34 business modem. The 3825Plus gives you data rates up to 33.6 Kbps in a compact, easy-to-use unit that measures just 6 x 9 inches. Designed especially for business use between remote home and small office users and their corporate network locations, the 3825Plus is packed with robust features. For example, the 3825Plus is completely software upgradeable and configurable, so your whole fleet of modems can take advantage of firmware upgrades and feature enhancements through simple software downloads that can be done via the telephone line! With the 3825Plus, you won't have to spend needless time and money replacing chips or sending units back for factory upgrades.

Managed by the COMSPHERE 6700 Network Management System (NMS), the 3825Plus is easy to maintain and support. The special security features of double passwords, call-back screening, and silent answering minimizes unauthorized users. Twenty-four-hour technical support ensures you'll get all the assistance you need to keep your modems up and running. By combining Software-Defined (SD) modem architecture and V.34 modulation, with competitive pricing, the 3825Plus is the perfect choice to meet your business' growing and changing network requirements. It is also the ideal solution for after-hours, telecommuting, and work-at-home business users.

FEATURES

- OPERATES AT SPEEDS UP TO 33.6 Kbps
- USER-FRIENDLY CONFIGURATION AND CONTROL CAPABILITIES VIA NMS OR AT COMMANDS
- ENHANCED ASYNCHRONOUS DATA PERFORMANCE WITH ITU V.42 bis OR MNP 5 DATA COMPRESSION
- COMPLETE, 100 PERCENT DATA INTEGRITY WITH ITU V.42 OR MNP 2-4 ERROR CORRECTION
- REMOTE CONFIGURATION, CONTROL, AND STATUS VIA THE COMSPHERE 6700 NMS OR A REMOTE 3800 CONTROL PANEL
- FULL COMPLEMENT OF SELF TESTS, LOCAL AND REMOTE LOOPBACKS, INCLUDING COMPLIANCE WITH ITU V.54
- SOFTWARE-DEFINED ARCHITECTURE FOR FIRMWARE AND OPTIONAL FEATURE DOWNLOADS
- MODULATES AT V.34, V.32terbo*, V.32 bis, V.32, V.22 bis, V.22, 212A, 103J, AND V.21
- DIALING CAPABILITIES INCLUDE ITU V.25 bis, AT COMMANDS, AND 6700 NETWORK MANAGEMENT
- CELLULAR DATA SUPPORT VIA ENHANCED THROUGHPUT CELLULAR (ETC®) PROTOCOL AVAILABLE AS AN OPTIONAL FEATURE
- FAX SUPPORTS GROUP 3, CLASS 1, AND CLASS 2 FAX

SPECIFICATIONS

Data Line Modulations

ITU V.34: 33.6 Kbps, 31.2 Kbps, 28.8 Kbps, 26.4 Kbps, 24 Kbps, 21.6 Kbps, 16.8 Kbps, 14.4 Kbps, 12 Kbps, 9.6 Kbps, 7.2 Kbps, 4.8 Kbps and 2.4 Kbps TCM synchronous/ asynchronous
V.32terbo*, 19.2 Kbps, 16.8 Kbps TCM, synchronous/ asynchronous

ITU V.32 bis, 14.4 Kbps, 12 Kbps, 9,600 bps, 7,200 bps TCM, 4,800 bps Quadrature Amplitude Modulation (QAM), synchronous/asynchronous
ITU V.32, 9,600 bps, 4,800 bps QAM, synchronous/asynchronous

ITU V.22 bis, 2,400 bps QAM, synchronous/ asynchronous

ITU V.22, 1,200 bps QAM, synchronous/asynchronous, Differential Phase-Shift Keyed (DPSK)
AT&T 212A 1,200 bps, synchronous/asynchronous, DPSK

AT&T 103J 300 bps, asynchronous, FSK

ITU V.21, 300 bps, asynchronous, FSK

Fax

Group 3, Class 1, Class 2, V.17, V.29, V.27 ter Quicklink II software included

Auto-Mode

V.34, V.32terbo*, V.32 bis, V.32, V.22 bis, V.22, AT&T 212A, 103J

Auto Rate (Fall back/forward)

33.6 Kbps, 31.2 Kbps, 28.8 Kbps, 26.4 Kbps, 24 Kbps, 21.6 Kbps, 19.2 Kbps, 16.8 Kbps, 14.4 Kbps, 12 Kbps, 9,600 bps, 7,200 bps, and 4,800 bps

DTE Rates (Asynchronous)

115.2 Kbps, 76.8 Kbps, 57.6 Kbps, 38.4 Kbps, 28.8 Kbps, 19.2 Kbps, 14.4 Kbps, 12 Kbps, 9,600 bps, 7,200 bps, 4,800 bps, 2,400 bps, 1,200 bps, and 300 bps

DTE Interface

EIA/TIA 232E/ITU V.24/ISO 2110

Special Functions

20-Number Password Access Security Directory

V.13 Simulated Carrier Control

V.14 Asynchronous-to-Synchronous Conversion
UNIX CD Wink

Power Requirements

117V AC + 10 percent, 60 Hz or 220-240V AC +/- 10 percent, 50 Hz or 60 Hz

Power Consumption

COMSPHERE 3825Plus (including power adapter-speaker off) uses 6 watts

Dimensions

Weight: 1.3 lbs. (shipping wt. 4.2 lbs.)

Height: 1.25 inches (3.0 cm)

Width: 6.0 inches (15 cm)

Depth: 8.75 inches (22 cm)

Error Control

ITU V. 42

MNP 2-4

Data Compression

ITU V.42 bis

MNP Class 5

Certification

Telco

FCC Part 68 (USA)

DOC (Canada)

Safety

UL (USA)

CSA (Canada)

Emissions

FCC Part 15, Subpart J, Class B AW2 3825

* V.32terbo is a Paradyne proprietary modulation.

A few more reasons to connect with Paradyne—the industry leader and winner of these awards for modern products.



MOD-3825-3-0398

For additional information on this or any Paradyne product or service, contact the office nearest you. Or, dial toll-free (USA) 800 PARADYNE or call 813 530-8623. Fax (USA) 813 530-8216.

Toronto 905 709-5000 fax: 905 709-3469
Hong Kong 852 2543-0083 fax: 852 2541-3767
Singapore 65 355-5230 fax: 65 355-5244
France 33 492 942-5000 fax: 33 492 942-501
China 8610 6499-1425 fax: 8610 6492-5915

Montreal 514 288-0001 fax: 514 288-1246
Japan 81 3-5541-6630 fax: 81 3-5541-6631
Latin America 813 530-8358 fax: 813 532-5240
Visit the Paradyne Power Pages at <http://www.paradyne.com>
Japanese Language website: www.paradyne.co.jp

Specifications subject to change without notice. Printed in U.S.A. ©Paradyne Corporation 1998.

COMSPHERE and ETC are registered trademarks of Paradyne Corporation. PARADYNE is a trademark of Paradyne Corporation. All other products or services mentioned are the trademarks, service marks, registered trademarks, or registered service marks of their respective owners.

PARADYNE™