



Z H O N E

IPD 4000E Broadband Loop Carrier (BLC)

IPD4000E

Video Ready, High-capacity Ethernet-based IP Broadband Loop Carrier for Central Office or Remote Terminal DSL deployments

- ✓ *DSL the Easy Way™ provides true 'Plug & Play', loop-bonded operation with no configuration required*
- ✓ *Compact system with 4 line card slots (up to 192 lines)*
- ✓ *High bandwidth, full duplex 8-GigE uplink and 8-GigE backplane capacities*
- ✓ *Choice of T1, E1, ADSL2+, SHDSL/SHDSL.bis, and Active Ethernet, hot-swappable, access modules*
- ✓ *Supports T1/E1 and SHDSL/SHDSL.bis loop bonding for high-capacity, symmetric business-class services*
- ✓ *Survivable network topology options based on RFC3619 EAPS rings*
- ✓ *Metro Ethernet Forum (MEF 9/14) Certified for EVPL and E-LAN Services*



Zhone's IPD4000E Broadband Loop Carrier (BLC) provides a high capacity, native IP Ethernet platform for the feature rich multi-service access multiplexer modules in the IPD family. It is a smaller and more compact version than the IPD12000E chassis, and is ideally suited for smaller central office or remote site applications requiring up to 192 subscriber lines.

The IPD4000E is engineered for efficient, high-speed IP data transport in a compact, fault-tolerant chassis. Supporting high-density Active Ethernet, ADSL2+, SHDSL, extended-rate SHDSL.bis, and T1/E1 access modules, the Ethernet-based IPD4000E is the optimal line aggregation platform for today's advanced IP-based access networks. Incumbents, Competitive Operators, and Internet Service Providers are able to cost-effectively offer the full range of today's advanced IP-based services, such as high-speed broadband Internet and IP video. Most importantly, these services can be delivered over a pure IP network without a dependency on ATM.

The IPD4000E features a high capacity backplane, delivering up to 2 Gbps throughput to each of the 4 access slots, and up to 8 Gbps upstream from a single Broadband Services Switch 8000 uplink cards. Dual 50-pin, RJ-21 connectors are provided for every access slot so that the chassis can support higher port density modules in any slot. High port density modules include a 48-port ADSL2+, a 48-port SHDSL.bis, and 24-port, 4-wire T1 and E1 modules. For mission-critical, high speed data applications, the IPD4000E offers a survivable network topology by means of Ethernet Automatic Protection Switching (EAPS) rings.

Managing all of these high-speed services could not be simpler with the availability of a full range of local and remote management options, including an integrated Web GUI, SNMP, and Command Line Interface (CLI). All of the Access Modules offer simple, 'Plug & Play' operation, with the system configuring each port automatically and without intervention. When more sophisticated bandwidth management functionality is desired, the IPD supports Zhone's complete Multi-media Traffic Management (MTM) feature set, giving system operators the ability to prioritize traffic based on DSCP, IP address ranges, MAC address ranges, and VLAN ranges. Rate limiting features and 802.1p priority also ensure that specific applications are given appropriate priority and bandwidth allocation throughout the system, while marking packets for appropriate VLAN and QoS management by upstream network devices.

The IPD4000E supports a single BSX8000-5 (Broadband Switch Modules) uplink card. The BSX8000 switch card supports four (4) Gigabit uplink ports, and has provisions for an optional MIM (Micro Interface Module), allowing the IPD to integrate easily into a variety of network designs. A variety of MIM types are available, including: 10/100 Ethernet; 100 Mbps fiber; 2 x T1/E1; 4 x T1/E1; and either 2- or 4- Gigabit Ethernet ports using either copper or fiber Small Form Factor Pluggable modules.

For installation flexibility, the IPD4000E is only 4-rack units high, and has removable mounting brackets that can be placed in increments of 1.45" up to 9.28" from the front of the chassis, allowing for multiple installation options in either 19" or 23" equipment racks.

Technical Specifications

Dimensions

- 4 Rack Units
- 7" H x 17" W x 18" D
- 17.8cm H x 43.2cm W x 46cm D

Weight

- 28 lbs (12.73 kg) (chassis only)

Power

- AC -- Requires External AC to -48 Volt DC Power Converter
- DC -- Redundant -48 VDC Terminal Blocks
- 10 A maximum; 5.5 A typical*
- *actual power consumption dependent upon chassis configuration

Interfaces

- 5 slot chassis:
 - 4 Access Module slots (front)
 - 1 Multiplexer Uplink Module slot (front)
 - 8 RJ-21 (50-pin) Telco Connectors (rear)

Regulatory Compliance

- NEBS: GR-63-CORE, GR-1089-CORE
- EMC: FCC Part 15; CSA/C108.8; EN55022; EN55024, CE Marking
- Safety: UL1950, CSA C22.2 No. 950; EN60950, CE Marking

Operating Requirements

- Temperature: 32°F to 122°F (0°C to 50°C)
- Non-operating temperature: -40°F to 158° F (-40°C to 70°C)
- Humidity: 5% to 95%, non-condensing
- Altitude: -200ft to 16,500ft (-60m to 5,000m)

Ordering Information

System Chassis

IPD4000E-19	IPD4000E chassis (4-Access Slots / 1-BSX Uplink Slot). Ships with 19" variable rack mounting brackets
IPD4000E-23	IPD4000E chassis (4-Access Slots / 1-BSX Uplink Slot). Ships with 23" variable rack mounting brackets
IPD4000E-RMB19	19" variable rack mount brackets for the IPD4000E (included with IPD4000E-19)
IPD4000E-RMB23	23" variable rack mount brackets for the IPD4000E (included with IPD4000E-23)

Uplink & Interface Modules

BSX8000-5	Broadband Services Switch 8000 for IPD 12000E/4000E (with EAPS support)
MIM	Micro Interface Modules (MIM) for the BSX8000-5

Access Modules

AEM100-16	16-port Active Ethernet Module for the IPD
AIM24000-48	48-port ADSL2+ Line Card (Conexant chipset)
AIM29000-48	48-port ADSL2+ Line Card (Broadcom chipset)
EIM2000-24	24-port E1 Inverse Multiplexer Module
ESIM5700-48	48-port Ethernet SHDSL.bis Inverse Multiplexer Module
SIM2000-24	24-port SHDSL Inverse Multiplexer Module
TIM1500-24	24-port T1 Inverse Multiplexer Module

Modular Power Converter

MPC	Modular AC-to-DC Power Converters
-----	-----------------------------------



Zhone Technologies, Inc.
 @ Zhone Way
 7001 Oakport Street
 Oakland, CA 94621
 510.777.7000 phone
www.zhone.com

For more information about Zhone and its products, please visit the Zhone Web site at www.zhone.com or e-mail info@zhone.com

Zhone, the Zhone logo, and all Zhone product names are trademarks of Zhone Technologies, Inc. Other brand and product names are trademarks of their respective holders. Specifications, products, and/or product names are all subject to change without notice.
 Copyright 2007 Zhone Technologies, Inc. All rights reserved.